



## JFGA.E335324 Fuses for Photovoltaic Systems

Page Bottom

### Fuses for Photovoltaic Systems

See General Information for Fuses for Photovoltaic Systems

**COOPER BUSSMANN L L C**  
114 OLD STATE RD  
ELLISVILLE, MO 63021 USA

E335324

Cat. No.	Interrupting Capacity			Rating		
	Volts		Amps	Volts		Amps
	DC	AC		DC	AC	
PVS-R 20 - 400	600	—	10,000	600	—	20-400
PV-xA10, where x is replaced with 1-12, followed by F, -T, -1P or -2P	1000	—	50,000	1000	—	1-12
PV-xA10, where x is replaced with 15, followed by F, -T, -1P or -2P	1000	—	50,000	1000	—	15
PV-xA10, where x is replaced with 13-20, followed by F, -T, -1P or -2P	1000	—	50,000	1000	—	13-20
PV-xxA14F, where xx is replaced with 15-32	1000	—	10,000	1000	—	15-32
PV-xxA14F, where xx is replaced with 15-20	1100	—	10,000	1100	—	15-20
PV-xxA14L, where xx is replaced with 15-20, followed by F, F10F, -T, or -TP	1500	—	10,000	1500	—	15-20
PV-xxA14L, where xx is replaced with 25-32, followed by F, F10F, -T, or -TP	1300	—	10,000	1300	—	25-32
PVM-3FS	1000	—	50,000	1000	—	3
PVM-3.5FS	1000	—	50,000	1000	—	3.5
PVM 4-30	600	—	50,000	600	—	4-30
PVCFxxxRN	600	—	50,000	600	—	1-100
PV-200A-1XL-B-15, PV-200A-1XL-15	1500	—	30,000	1500	—	100-200
PV-xxxA-01XL, where xxx is replaced with 63-160. May be followed by -B	1000	—	50,000	1000	—	63-160
PV-xxANH1, where xx is replaced with 32-50	1000	—	50,000	1000	—	32-50
PV-xxxANH1, where xxx is replaced with 63-160	1000	—	50,000	1000	—	63-160
PV-xxxA-1XL, where xxx is replaced with 100-200. May be followed by -B	1000	—	33,000	1000	—	100-200
PV-xxxA-2XL, where xxx may be followed by 160-355. May be followed by -B, -E or -EKW	1000	—	33,000	1000	—	160-355
PV-xxxA-3L, where xxx may be followed by 355- 630. May be followed by -B	1000	—	50,000	1000	—	355-630
PV-xxxA-01XL-15, PV-xxxA-01XL-B-15 where xxx is replaced with 50-125.	1500	—	30,000	1500	—	50-125
PV-xxxA-01XL-11, PV-xxxA-01XL-B-11 where xxx is replaced with 50-125.	1100	—	30,000	1100	—	50-125
PV-xxxA-01XL-12, PV-xxxA-01XL-B-12 where xxx is replaced with 160.	1200	—	30,000	1200	—	160
PV-xxxA-3L-B-15, where xxx is replaced by 250-400, (-B is optional)	1500	—	30,000	1500	—	250-400
PV, Series PV-xxxA-2XL-B-15, PV-xxxA-2XL-15	1500	—	30,000	1500	—	250
PV-xxxA-2XL-B-11, PV-xxxA-2XL-11	1100	—	30,000	1100	—	250

Last Updated on 2013-01-18

[Questions?](#)[Print this page](#)[Terms of Use](#)[Page Top](#)

© 2013 UL LLC

When the UL Leaf Mark is on the product, or when the word "Environment" is included in the UL Mark, please search the [UL Environment database](#) for additional information regarding this product's certification.

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured

under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2013 UL LLC".