



HELUKABEL JZ-500 black 25G1,5QMM/10371 300/500V 0010917711 CE



Technical data

- Control cables, special PVC adapted to DIN VDE 0285-525-2-51 / DIN EN 50525-2-51
- **Temperature range**
flexing -15°C¹⁾ to +80°C
fixed installation -40°C to +80°C
- **Nominal voltage** U₀/U 300/500 V
- **Test voltage** 4000 V
- **Breakdown voltage** min. 8000 V
- **Insulation resistance**
min. 20 MOhm x km
- **Minimum bending radius**
flexing 7,5x cable Ø
fixed installation 4x cable Ø
- **Radiation resistance**
up to 80x10⁶ cJ/kg (up to 80 Grad)
- ¹⁾ Cold bending-, Impact resistance-, Elongation test to
DIN VDE 0473-811-504 /-505 /-506
DIN EN 60811-504 /-505 /-506

Cable structure

- Bare copper, fine wire conductors, according to DIN VDE 0295 cl. 5, BS 6360 cl. 5 and IEC 60228 cl. 5
- Core insulation of special PVC Z 7225
- Black cores with continuous white numbering according to DIN VDE 0293
- Green-yellow earth core in the outer layer (3 cores and above)
- Cores stranded in layers with optimal lay-length
- Outer sheath of special PVC, TM2 to DIN VDE 0207-363-4-1 / DIN EN 50363-4-1
- colour black (RAL 9005)
- with meter marking

Properties

- Extensively oil resistant, oil-/ chemical Resistance - see table Technical Informations
- PVC self-extinguishing and flame retardant according to DIN VDE 0482-332-1-2, DIN EN 60332-1-2 / IEC 60332-1 (equivalent DIN VDE 0472 part 804 test method B)
- The materials used in manufacture are cadmium-free and contain no silicone and free from substances harmful to the wetting properties of lacquers
- **UV- resistant**

Note

- G = with green-yellow earth core;
x = without green-yellow earth core (OZ).
- AWG sizes are approximate equivalent values. The actual cross-section in mm².
- screened analogue type:
JZ-500-C black

Application

These cables are used for flexible use for medium mechanical stresses with free movement without tensile stress or forced movements in dry, moist and wet rooms and **in open air**. Must not be laid directly in soil or water. When screened for measurement, control and control line etc. in mechanical and plant engineering, machine tools, production lines and conveyor belts.

CE= The product is conformed with the EC Low-Voltage Directive 2006/95/EC.

Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
10340	2 x 0,5	5,5	9,6	40,0	20
10341	3 G 0,5	5,8	14,4	46,0	20
10342	4 G 0,5	6,2	19,0	56,0	20
10343	5 G 0,5	6,9	24,0	65,0	20
10344	7 G 0,5	7,5	33,6	80,0	20
10345	12 G 0,5	9,8	58,0	135,0	20
10346	18 G 0,5	11,8	86,0	196,0	20
10347	25 G 0,5	13,7	120,0	270,0	20
1034	2 x 0,75	5,9	14,4	46,0	19
10349	3 G 0,75	6,2	21,6	54,0	19
1035	4 G 0,75	6,7	28,8	66,0	19
10351	5 G 0,75	7,5	36,0	80,0	19
1035	7 G 0,75	8,3	50,0	110,0	19
10353	12 G 0,75	10,8	86,0	179,0	19
1035	18 G 0,75	12,8	130,0	257,0	19
1035	25 G 0,75	15,1	180,0	365,0	19
1035	2 x 1	6,2	19,2	60,0	18
1035	3 G 1	6,5	29,0	72,0	18
1035	4 G 1	7,2	38,4	86,0	18
10359	5 G 1	7,9	48,0	104,0	18
1036	7 G 1	8,7	67,0	141,0	18
10361	12 G 1	11,4	115,0	230,0	18
10362	18 G 1	13,7	173,0	343,0	18
10363	25 G 1	16,2	240,0	485,0	18
10364	2 x 1,5	7,0	29,0	70,0	16

Part no.	No. cores x cross-sec. mm ²	Outer Ø approx. mm	Cop. weight kg / km	Weight approx. kg / km	AWG-No.
10365	3 G 1,5	7,4	43,0	90,0	16
10366	4 G 1,5	8,2	58,0	109,0	16
10367	5 G 1,5	9,1	72,0	131,0	16
10368	7 G 1,5	9,8	101,0	184,0	16
10369	12 G 1,5	13,6	173,0	309,0	16
10370	18 G 1,5	15,6	259,0	440,0	16
10371	25 G 1,5	18,4	360,0	620,0	16
10372	2 x 2,5	8,4	48,0	112,0	14
10373	3 G 2,	8,9	72,0	148,0	14
10374	4 G 2,5	9,8	96,0	178,0	14
10375	5 G 2,	10,9	120,0	221,0	14
10376	7 G 2,5	12,0	168,0	306,0	14
10377	12 G 2,5	15,9	288,0	498,0	14
10378	18 G 2,5	19,0	432,0	764,0	14
10379	25 G 2,5	22,6	600,0	1044,0	14
10380	4 G 4	11,6	154,0	295,0	12
10381	5 G 4	12,9	192,0	361,0	12
10382	4 G 6	13,1	230,0	424,0	10
10383	5 G 6	14,5	288,0	525,0	10
10384	4 G 10	17,0	384,0	701,0	8
10388	5 G 10	18,9	480,0	909,0	8
10385	4 G 16	20,9	614,0	1035,0	6
10386	4 G 25	25,6	960,0	1582,0	4
10387	4 G 35	30,0	1344,0	2105,0	2

Dimensions and specifications may be changed without prior notice. (RA01)